GTE



RACK & DATA CABINET













General

GTE Data Cabinets & Racks are Born from an innovative while you benefit from integrated engineering solutions based on top-quality system components, component data, system know-how and design expertise throughout every aspect of GTE cabinets. It is a "state of the art" cabinet that satisfy the needs of structured cabling, as well as IT and video surveillance.

Features:

- 19" Well designed frame with precise dimensions.
- Toughened glass front door with door border and steel Side door.
- Several Cable Entries on top cover and bottom Panel with adjustable sizes.
- Meeting requirements of under-Base Cable entry/ventilation and prevention.
- Removable Side Panels, easy to install and maintain
- Standing or wall mounting installation
- Adjustable feet and heavy duty castors are optional
- Easy mounting installation.
- Adjustable feet as standard; castors, lockable castors, plinth,
- plinth with filter optionally
- GND/earthling kit.
- Racks can be installed in blocks

Standards:

Comply with ANSI/EIA RS-310-D , IEC297-2 , DIN41491;Part1 , DIN41494;Part7 , GB/T3047.2-92 & EIA Standard





Loading Capacity:

Static Loading: up to 220 Kg for Wall Mounted and up to 1250 Kg for Free Stand

Degree of Protection:

Standard protection rating IP20 IP40 on Request

Material:

Cold Rolled Steel 1.2mm & 1.5mm for WM 1.5mm & 2.0mm for FS

Surface Finishing:

Power coated with RAL Color7032, 7035, 7038, 9003, 9005 and others.

Cable Entry

Bottom and/or Top, rear door



4 Free Stand Cabinets

| Cabinet Size | Width "W" | Depth "D" | Height "H" | Model No. |
|-----------------|--------------|--------------|---------------|-------------------|
| 22 | 600 | 600 | 1015 | GE-Y-FS-22U-6-6 |
| 22 | 600 | 800 | 1015 | GE-Y-FS-22U-6-8 |
| 24 | 600 | 600 | 1150 | GE-Y-FS-24U-6-6 |
| 24 | 600 | 800 | | GE-Y-FS-24U-6-8 |
| | 600 | 600 | | GE-Y-FS-27U-6-6 |
| 27 | 600 | 800 | 1280 | GE-Y-FS-27U-6-8 |
| | 600 | 1000 | | GE-Y-FS-27U-6-10 |
| | 800 | 800 | | GE-Y-FS-27U-8-8 |
| | 800 | 1000 | | GE-Y-FS-27U-8-10 |
| | 600 | 600 | 1500 | GE-Y-FS-32U-6-6 |
| 32 | 600 | 800 | | GE-Y-FS-32U-6-8 |
| | 600 | 1000 | | GE-Y-FS-32U-6-10 |
| | 800 | 800 | | GE-Y-FS-32U-8-8 |
| | 800 | 1000 | | GE-Y-FS-32U-8-10 |
| | 600 | 600 | 1680 | GE-Y-FS-36U-6-6 |
| 36 | 600 | 800 | | GE-Y-FS-36U-6-8 |
| | 600 | 1000 | | GE-Y-FS-36U-6-10 |
| | 800 | 800 | | GE-Y-FS-36U-8-8 |
| | 800 | 1000 | | GE-Y-FS-36U-8-10 |
| | 600 | 600 | 1950 | GE-Y-FS-42U-6-6 |
| 42 | 600 | 800 | | GE-Y-FS-42U-6-8 |
| | 600 | 1000 | | GE-Y-FS-42U-6-10 |
| | 800 | 800 | | GE-Y-FS-42U-8-8 |
| | 800 | 1000 | | GE-Y-FS-42U-8-10 |
| | 800 | 1200 | | GE-Y-FS-42U-8-12 |
| | 1000 | 1000 | | GE-Y-FS-42U-10-10 |
| | 600 | 600 | 2070 | GE-Y-FS-45U-6-6 |
| | 600 | 800 | | GE-Y-FS-45U-6-8 |
| 45 | 600 | 1000 | | GE-Y-FS-45U-6-10 |
| | 800 | 800 | | GE-Y-FS-45U-8-8 |
| | 800 | 1000 | | GE-Y-FS-45U-8-10 |
| | 600 | 600 | 2170 | GE-Y-FS-48U-6-6 |
| 48 | 600 | 800 | | GE-Y-FS-48U-6-8 |
| | 600 | 1000 | | GE-Y-FS-48U-6-10 |
| | 800 | 800 | | GE-Y-FS-48U-8-8 |
| | 800 | 1000 | | GE-Y-FS-48U-8-10 |
| | 800 | 1200 | | GE-Y-FS-48U-8-12 |



| Front Door | Side Door | Back Door |
|--|-------------|--|
| solid Steel | Solid Steel | Solid Steel |
| Glass | | Glass |
| Fully Perforated | Perforated | Fully Perforated |
| Solid Steel with Top/Bottom Perforated | | Solid Steel with Bottom Perforated |




Door Specs:


- Perforated Metal Door: High-Flow Perforated Metal
- Door provides the security of a solid metal door with xx% airflow. Use High-Flow Perforated Metal Door on the front or rear of cabinets to encourage front-to-rear airflow through rack mount Equipment.
- Doors can be made to be reversible to open right or left



















Cantilever Shelf



Cantilever Shelf

Cable Management

Horizontal Cable management for ease patching Vertical Cable Management for FS cabinets

Power Strip

Different Types of PDU as per request

- Universal Socket (Standard)
- UK Socket

Shelves

- a) Fixed
- b) Telescopic
 - Made of 2 mm sheet steel
 - Whole surface is perforated for effective
 - Ventilation

Fan Tray

Easy assembled to the top sheet with on/off switch, thermostat for temperature control. Long life, quiet and reliable.

No. of fan:

1 Fan

2 Fan

4 Fan

Cantilever Shelf